

Heavy-duty overhead door holder and stop for exterior, vestibule or interior doors, either single or double acting

**Now available
US32D & US32**

**1000 ADJ SERIES
CONCEALED**



STANDARD FEATURES

- For All Stainless Steel Components - Prefix N
- Non-handed/reversible
- Single point hold-open is field adjustable from from 85° to 110°
- Hold-open knob can be disengaged to act as a stop only
- 5° to 7° shock compression following hold-open point
- Steel shock absorbing spring
- Die cast end block and shock block
- Maximum opening 110°, minimum door thickness 1 3/4"
- Both wood and machine screws included
- Available in all BHMA plated and sprayed finishes

**All Stops
Warnock Hersey
listed**

**WHEN ORDERING,
please list:**

Model number

Door closer number or other hardware

Mounting means of the door and butt size

Hold-open or dead-stop degree

Door opening and thickness

Finish

SPECIFICATIONS:

Stop only function to be Warnock Hersey listed as manufactured by ABH.

*Material:
steel/stainless steel channel
3/32" thick and 1 1/8" depth;
arm 1/4" thick and 1" wide;
jamb track 1 1/4" wide; sliding
block shall have easy access
for tension adjustment.*

DOOR FRAME OPENING	HOLDER NUMBER		
BUTTS OFFSET PIVOTS	HOLD- OPEN	STOP	FRICTION
27" - 29 15/16"	1011A	1021A	1031A
30" - 35 15/16"	1012A	1022A	1032A
36" - 39 15/16"	1013A	1023A	1033A
40" - 43 15/16"	1014A	1024A	1034A
44" + Greater	1015A	1025A	1035A
BHMA NUMBER	C01511	C01541	C01531
FED. SPEC TYPE	1160	—	—

Contact ABH for special templating or other door opening
Average weight/unit 6 lbs.

www.abhmfg.com
E-mail: abhinfo@abhmfg.com
Architectural Builders Hardware Mfg., Inc.
 1222 Ardmore Ave., Itasca, IL 60143
630.875.9900; FAX 800.9FAXABH (932.9224)

© 2005 ABH Mfg., Inc.
Printed in USA 02/05

