

Heavy-duty overhead door holder or stop for exterior, vestibule or interior doors, either single or double acting

**Now available
US32D & US32**

**1000 SL SERIES
SLIM LINE CONCEALED**



STANDARD FEATURES

- Non-handed/reversible
- Single point hold-open in increments of 5° from 85° to 110°
- 5° to 7° shock compression following hold-open point
- Steel shock compression spring
- For doors hung on butts, offset and center hung pivots
- Maximum opening 110°, minimum door thickness 1 3/4"
- Both wood and machine screws included
- Available in all BHMA plated and sprayed finishes
- 1/2" maximum channel depth

**All Stops
Warnock Hersey
listed**

**WHEN ORDERING,
please list:**

Model number

Door closer number or other hardware

Mounting means of the door and butt size

Hold-open or dead-stop degree

Door opening and thickness

Finish

SPECIFICATIONS:

Stop only function to be Warnock Hersey listed as manufactured by ABH.

*Material:
steel/stainless steel channel
1/8" thick and 1/2" depth; arm
1/4" thick and 1" wide; jamb
bracket 1" wide and 1/4"
thick; sliding block for hold-
open mechanism.*

DOOR FRAME OPENING		HOLDER NUMBER	
BUTTS OFFSET PIVOTS	CENTER HUNG	HOLD-OPEN	STOP
27" - 29 15/16"	30" - 32 15/16"	1011SL	1021SL
30" - 35 15/16"	33" - 38 15/16"	1012SL	1022SL
36" - 39 15/16"	39" - 42 15/16"	1013SL	1023SL
40" - 43 15/16"	43" - 46 15/16"	1014SL	1024SL
44" + GREATER	47" + GREATER	1015SL	1025SL
BHMA NUMBER		C01511	C01541
FED. SPEC TYPE		1160	—

Contact ABH for special templating or other door opening
Average weight/unit 6 lbs.

www.abhmfg.com
E-mail: abhinfo@abhmfg.com
Architectural Builders Hardware Mfg., Inc.
1222 Ardmore Ave., Itasca, IL 60143
630.875.9900; FAX 800.9FAXABH (932.9224)

© 2005 ABH Mfg., Inc.
Printed in USA 02/05

