

Extra heavy-duty and heavy-duty overhead door holder/stop for exterior, vestibule and interior doors, single acting

**Now available
US32D & US32**

**8000 SERIES
SURFACE MOUNTED**



STANDARD FEATURES

- Non-handed/reversible
- Single point hold-open in increments of 5° from 85° to 110°
- Hold-open holder shall engage and release door automatically by brass/stainless steel handle, or act as a stop only
- Maximum opening 110°, minimum door thickness 1 1/4"
- Wood, machine screws and sex bolts included
- Available in all BHMA finishes
- For extra heavy duty add **HD** before holder number. Four sex bolts provided for the door portion.

**All Stops
Warnock Hersey
listed**

**WHEN ORDERING,
please list:**

Model number

Door closer number or other hardware

Mounting means of the door and butt size

Hold-open or dead-stop degree

Door opening and thickness

Finish

SPECIFICATIONS:

Stop only function to be Warnock Hersey listed as manufactured by ABH.

*Material:
Housing 1/8" thick; arm 1/4" thick and 1" wide; jamb bracket 1/4" thick and 1" wide. Hold-open mechanism-stop PIN #303 stn. steel; lock plate case harden .0101 to .012 deep.*

DOOR FRAME OPENING		HOLDER NUMBER	
BUTTS OFFSET PIVOTS	CENTER HUNG	HOLD-OPEN	STOP
27" - 32 7/16"	29 1/2" - 34 15/16"	8010	8020
32 1/2" - 38 11/16"	35" - 41 7/16"	8011	8021
38 3/4" - 42 7/16"	41 1/2" - 44 15/16"	8012	8022
42 1/2" + Greater	45" + Greater	8013	8023
BHMA NUMBER		C03511	C03541
FED. SPEC TYPE		GJ80	GJ80

Contact ABH for special templating or other door opening
Average weight/unit 4 1/2 lbs.

www.abhmfg.com
E-mail: abhinfo@abhmfg.com
Architectural Builders Hardware Mfg., Inc.
1222 Ardmore Ave., Itasca, IL 60143
630.875.9900; FAX 800.9FAXABH (932.9224)

© 2005 ABH Mfg., Inc.
Printed in USA 02/05





REVERSIBLE


8000/HD8000 SERIES HOLDERS & STOPS

FOR SINGLE ACTING DOORS ONLY

NON - HANDED



FOR 8000 USE (2) INNER MOUNTING HOLES
FOR HD8000 USE (4) MOUNTING HOLES



SCREW DETAIL			
	QTY	WOOD	METAL
JAMB	4	(2) #8x3/4" F.H.W.S.	(2) 12-24 X 3/8" F.H.W.S.
DOOR	2	1/4-20 X 1-1/2" RD.H.M.S 3/8" D. SEX BOLT	1/4" -20 X 1-1/2" RD.H.M.S 3/8" D. SEX BOLT
DOOR	4	1/4-20 X 1-1/2" RD.H.M.S 3/8" D. SEX BOLT	1/4-20 X 1-1/2" RD.H.M.S 3/8" D. SEX BOLT

DO NOT SCALE DRAWING
ALWAYS REQUEST LATEST TEMPLATE
FOR NEW INSTALLATION
ALL DIMENSIONS SHOWN IN INCHES

www.abhmfg.com
E-mail: abhinfo@abhmfg.com
Architectural Builders Hardware Mfg., Inc.
 1222 Ardmore Ave., Itasca, IL 60143
630.875.9900; FAX 800.9FAXABH (932.9224)

© 2005 ABH Mfg., Inc.
Printed in USA 02/05

