

Overhead Holders & Stops



Innovation, Quality,
Customer Service...

3500 Series Surface Mount, Parallel Arm Holder



Standard Features

- Surface mount
- Heavy duty
- Adjustable hold-open position from 135° to 180°
- Single acting doors only
- For use on the inactive leaf of a pair of doors where a door closer is installed on the active leaf
- For interior or exterior use on frequent traffic and heavy weight doors
- For door openings 24" - 36"
- Units are handed - specify when ordering
- Standard fasteners supplied for 1-3/4" to 1-7/8" thick door (see options for other door thicknesses)
- Average weight per unit = 4 lbs.

Options Available

(see page B-5 for details)

- **THICK** - Fasteners for doors other than 1-3/4" to 1-7/8" thick - Specify door thickness
- **SNB** - Sex bolts provided for door portion screw detail
- **SEC** - Security fasteners
- **LL** - For lead-lined door applications
- **SPECIAL** - Contact ABH if the dimensions, hardware or specifications differ from what is shown on the template or if additional hardware is being used at the top of the door. A custom template and/or unit may be required.
- If using a closer, please go to our website and reference "ABH Overhead Holder & Stop Compatibility Chart" to determine possible conflict.

Material

- **Aluminum die casting** is the standard base material for arms and jamb bracket for all finishes.

Specify When Ordering

- Model Number
- Handing
- Finish
- Option(s), if applicable

Door Frame Opening	Model Number
Butts or Offset Pivots	Hold Open
24" - 36"	3500

