


## 6100 Series - Retrofit Application Cylindrical Latches

Innovation, Quality,  
Customer Service...

### Standard Features

- Specifically designed for retrofit application with an existing 161 prep or in new construction when drilling additional holes for thru-bolt mounting is undesirable
- Locks and functions identical to 6000 series, except all mounting hardware goes through the standard 161 prep and does not require any additional door prep for installation (no additional four thru-bolts holes).
- Cylindrical latch application – passage function
- 1-3/4" standard door thickness (specify if different)
- Meets ADA requirements
- One continuous spring provides a smoother operation and extended life for the unit
- Non-handed unit for installation and stocking ease
- Trim can be mounted vertical or horizontal (with handles pointing toward hinge edge of door)
- Handles can be mounted up or down by simply rotating trim 180°
- UL Listed in U.S.A and Canada for use on door fire rated 90 minutes or less, up to 4'0" x 8'0"
- 1/2" Latch Bolt Throw
- Patents# 6,196,599 & #5,730,478



### How to Order:

**Example: 61 2 A - US32D - AM**

**Model:** \_\_\_\_\_

- 61 = 6100 Series

**Latch Backset:** \_\_\_\_\_

- 2 = 2-3/4"    • 5 = 5"
- 3 = 3-3/4"    • 7 = 7"

**Strike:** \_\_\_\_\_

- T = 2-3/4" T-Strike
- A = 4-7/8" ASA Strike

**Finish:** \_\_\_\_\_

- US32D • US32 • US10B • US3
- US26D • US26 • US10 • US4

**Options, if Needed:** \_\_\_\_\_

- AM • L • PL • PS • H • EX
- X • J • RC • SEC • THICK • P

(See pages C-3 to C-5 for details)

