

## Non - Electrical Options

### “CUT” - Cut to Custom Length

If a non-standard length hinge is required, ABH will cut from the bottom of the hinge to the desired length as long as it does not interfere with a screw hole. **Specify length and handing.**

### “SPLICE” - Spliced Hinge

For hinges exceeding 118-3/4”, ABH splices two separate lengths with an alternately split stainless steel pin that holds the barrel together. **Specify length and handing.**

### “HT” - Welded Hospital Tip

Top of the hinge barrel is cut at a 45° angle and then welded to help provide and support a safer environment in hospitals and other institutions. **Specify handing.**

### “DD” - Dutch Door

Modified door leaf cut to fit a dutch door application. Go online for order form or, specify top and bottom door leaf heights as well as clearance required between top and bottom and handing when ordering.

### “STUD” - Security Studs

1/2” diameter stainless steel studs are permanently mounted to the frame leaf projecting 1/4” and extend into the door leaf for added security.

### “AS” - Adjustable Studs

Threaded studs are supplied for hinges with door edge guards on both faces of the door to help correct door alignment issues up to 3/8”. Additional door reinforcement required. **Specify wood or metal door.**

### “SEC” - Security Fasteners

Security fasteners are supplied in lieu of standard fasteners for all exposed areas. **Specify wood or metal door and frame**

### “SNB” - Sex Bolts

When using on wood doors, sex bolts are provided for the surface mounted door portion.

### “LL” - Lead-Lined

Lead is provided for the door portion fastener cover for half surface and full surface hinges.

### “SL” - Sheared Leaf

Concealed leaf is sheared to accommodate a 1-3/8” thick door.

### “ADB” - Cut for Automatic Door Bottom

Specify automatic door bottom model when ordering.

### “CUSTOM HOLE”

Contact factory with custom mounting hole locations desired for unusual frame and/or door conditions. Restrictions apply.

### “NO HOLE”

Contact factory for hinge without mounting holes.

### “CUSTOM FINISH”

Custom powder coated finishes available – contact factory for details. Customer color sample approval will be required prior to fabrication.

Non-Electrical Options - Compatibility Chart		CUT	SPLICE	HT	DD	STUD	AS	SEC	SNB	LL	SL	ADB	CUSTOM	NO HOLES	CUSTOM
Full Concealed	A500	•	•	•	•	•	•	•	•	•	•	•	•	•	•
	A500RB	•	•	•	•	•	•	•	•	•	•	•	•	•	•
	A500VV	•	•	•	•	•	•	•	•	•	•	•	•	•	•
	T	•	•	•	•	•	•	•	•	•	•	•	•	•	•
	A505	•	•	•	•	•	•	•	•	•	•	•	•	•	•
	A505RB	•	•	•	•	•	•	•	•	•	•	•	•	•	•
	A510	•	•	•	•	•	•	•	•	•	•	•	•	•	•
	A511	•	•	•	•	•	•	•	•	•	•	•	•	•	•
	A515	•	•	•	•	•	•	•	•	•	•	•	•	•	•
	A515RB	•	•	•	•	•	•	•	•	•	•	•	•	•	•
	A526	•	•	•	•	•	•	•	•	•	•	•	•	•	•
	A529	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Half Mortise	A5500	•	•	Standard	•	•	•	•	•	•	•	•	•	•	•
	A5515	•	•	•	•	•	•	•	•	•	•	•	•	•	•
	A5505	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Half Surface	A504	•	•	•	•	•	•	•	•	•	•	•	•	•	•
	A506	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Full Surface	A503	•	•	•	•	•	•	•	•	•	•	•	•	•	•
Full Surface	A502	•	•	•	•	•	•	•	•	•	•	•	•	•	•

